

산소 측정기 (O2 (DO) 메타)

Model Triton DO9 trace DO2 sensor



**Model Triton® DO9
ppb Dissolved Oxygen**

Features

- Large Measurement Range
- 3 Electrode Potentiostatic Measurement
- Long maintenance intervals
- Easy Calibration
- Digital Signal

센서 사양(Specifications).

- 0.001 to 20.00 mg/L for Maximum Accuracy
- Long term stability
- Drift < 1% per Month
- Air Calibration Only, No Zero Calibration Needed
- Noise Free signal, Calibration Stored in the Sensor

Model C22 galvanic DO

제품의 기능 및 사양

- . lead anode, silver cathode and Teflon membrane.
- . 4-20mA Isolated Out put(Hart, RS232 Option.)
- . Relay 단자 지원.
- . 쉬운 세정 및 유지관리.
- . Pipe, Wall, Handrail.Panel Mounting Type
- . NEMA 4X 규격의 방수형 케이스.
- . 멀티체널 가능.
- . 2.5" * 1.75" LCD Display.
- . 제품 크기 :
14.4cm(L)*14.4cm(W)*17.8cm(D)
- . 전원 : 110/220V@50Hz-60Hz
- . 동작온도 : -20°C to 70°C



센서 사양(Specifications).

측정 범위

0 - 20mg/L(0 - 20ppm)

0 - 250% 포화

압력 범위

최대 압력 4.5bar(50psi)

온도 범위

-5 to 80°C



넥서스테크놀로지스(주)